



Product Overview

8FE (PoE) +2GE is Unmanaged PoE contains 8 *10/100MbpsRJ45 ports and 2*10/100/1000MbpsRJ45ports, 1~8 support PoE functions. The PoE ports can automatically detect and supply power to IEEE802.3af/at compliant Powered Devices (PD). The electrical power and data transmission on the same cable can expand your network to the places where no power lines or outlets, where you can install devices such as APs, IP cameras, or IP phones etc.

8FE (PoE) +2GE has VLAN function which can improve the network environment and reduces network maintenance costs. It is easy to manage and maintain which can meet a lot of networking environment, such as Business building, Community, Hotel, Office etc.

Product Features

- Support IEEE802.3 at standard, compatible with IEEE802.3 af by electrical equipment (PD);
- Stand-up output power up to 32W;
- Support IEEE802.3 x full duplex flow control and Backpressure half duplex flow control;
- Panel lights to monitor working state and help fault analysis;
- Perfect security mechanism;
- Line-speed forwarding intelligent identification;
- Support VLAN and CCTV Function;
- Power supply, PoE module and switch PCBA Three in one.

Product Specifications

Model	8FE (PoE) +2GE
Interface	8*10/100Mbps RJ45 port 2*10/100/1000Mbps RJ45 port
PoE standard	IEEE802.3af/at
PoE port	1~8 port
PoE total	120W
Power supply	120W
Key function	CCTV&VLAN
RJ45 PoE power supply	Mode A Anode1/2 Cathode3/6
PoE output-port	Max 32W
Indicator	PWR (Green) LNK/ACT (Green) PoE (Orange) Speed(Green)
Network media	10BASE-T: UTP category 3,4,5 cable (≤100m) 100BASE-TX: UTP category 5, 5e cable (≤100m) 1000BASE-T: UTP category 5e,6 cable(≤100m) 100BASE-FX: SMF, MMF 1000BASE-X: SMF, MMF
MAC Address Table	4K, Automatic study, automatic updates
jumbo frame	9216Bytes
Packet buffer	2 Mbit
Transfer Mode	store-and-forward
Packet forwarding rate	4.16Mpps
Bandwidth	5.6Gbps
Fan	Fanless
Device Dimension	220*150*44mm
Machine weight	> 1kg
mains input	100~240V AC, 50/60Hz
Operating Temperature	0°C ~ 40 °C
Storage Temperature	-40 °C ~ 70 °C
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	5% ~ 90% non-condensing
Surge Protection	±4KV
Certification	CE、FCC ClassA
MTBF	>50000 hour
Electrostatic standard	Contact 6KV,air 8KV

Ordering information

Model	product information
8FE (PoE) +2GE	8*10/100Mbps+2GE Uplink PoE Switch